

# **KC50 Android Kiosk Computer**

### Designed for consumers, built for business, with the ultimate in flexibility

The KC50 Android Kiosk Computer is the heart of the versatile Zebra Kiosk System — a comprehensive, flexible and modular solution created to meet a wide variety of self-service, assisted checkout and display needs across industries, from retail and hospitality to healthcare, manufacturing, travel, government and more. Customers are instantly comfortable and ready to interact with the modern and elegant design. The KC50 is designed for consumers on the outside and built for business on the inside, based on the same proven Zebra enterprise Android platform at work in millions of Zebra's tablet, handheld and wearable mobile computers all around the world. The KC50 can be placed in portrait or landscape mode and mounted on a wall, floor, counter or desk. This modular solution allows you to add whatever your kiosk requires — a barcode scanner, printer, light bar, payment terminal, TD50 companion touch display and more. And support for a conversational digital assistant gives you more ways to interact with your customers.



# Rapid consumer adoption with alluring and intuitive consumer design

### Inviting consumer design

The modern KC50 was created with the customer in mind. The eye-catching design invites your customers to interact. And the bright screen is easy to see in any environment.

### Accessibility for all

The flexible mounting system makes it easy to create kiosks that are accessible to all, helping your business comply with the American Disabilities Act (ADA) in the United States, the European Accessibility Act (EAA), the Accessible Canada Act (ACA) and other international organizations.

# Create the perfect kiosk with a flexible modular design

### Choose your size, orientation and peripherals

These 15-inch and 22-inch displays can be deployed in either portrait or landscape orientation. The Z-Flex Connectors on each of the four sides are ready to connect peripherals, such as a scanner and a notification light bar. Since there is a universal Z-Flex connector on every side, peripheral placement is not restricted — and can be moved to another location at any time.

### Versatile mounting options

Different mounting configurations make it easy to place your Zebra Kiosk System wherever you need it. Mount it on a wall, or choose a modular stand system to deploy on a floor, counter or desk. The stands can house additional peripherals, such as a power brick or a printer. And with the TD50 touch display, you can create a double-sided kiosk that allows customers to review transactions.

### Add a digital assistant for conversational self-service

Sometimes a customer wants to ask a person a question instead of trying to find assistance within an app. Zebra's platform Application Programming Interfaces (APIs) enable integration of a conversational digital assistant. Designed with voice in mind, two integrated noise canceling microphones and dual 1W speakers ensure ample audio volume and clarity — even in noisy environments.



Power your Zebra Kiosk System with the KC50 flexible kiosk computer that's designed for consumers and built for business.

For more information, please visit www.zebra.com/kc50 or www.zebra.com/kiosk-system

### Empower your kiosk with integrated flawless scanning

Want to enable your customer to scan a loyalty or ID card, ticket and more? Just add a removable Zebra SE4720 scanner into a Z-Flex connector or pair with any Zebra Bluetooth or USB handheld scanner. Use the same familiar Zebra DNA tools to configure and deploy Zebra scanners — including DataWedge to easily enable your applications to capture barcode information, without writing any code. Regardless of which Zebra scanner you choose, you can count on the reliable capture of just about any barcode in virtually any condition for hassle-free self service.

### **Payment ready**

Enable payment with leading third party payment terminals mounted alongside the kiosk via a dedicated USB connection. And meet all of your card-reading needs with future support for Zebra Pay<sup>™</sup>, Zebra's comprehensive solution that includes everything required to accept any card-based payment.

## Beyond payment — enable contactless tap-to-transact with the many non-payment items in digital wallets

With support for Apple VAS and Google Smart Tap, customers can just tap to use the many items stored in their digital wallets, including event tickets, boarding passes, loyalty and gift cards, healthcare ID cards, mobile drivers license and more. Zebra's Apple VAS/Google Smart Tap Software Development Kit (SDK) simplifies integration and shortens development time — no specialized Apple VAS or Google Smart Tap protocol knowledge is required.

### Built for all-day everyday use

### A modern enterprise Android platform to power any application

Power multiple processing intensive applications with a powerful processor and large memory space. Simplify kiosk configuration with Mobility Extensions (Mx), included with every KC50. For example, with Zebra OEM Config, IT administrators can configure all KC50 features through their Enterprise Mobility Management (EMM) system without any proprietary integration or coding — including screen brightness settings, power settings, device I/O ports, Power-over-Ethernet (PoE) power profiles and more.

### Rock solid, fast Wi-Fi 6E connectivity

Wi-Fi connectivity gives you the flexibility to place kiosks wherever you want — but you can't compromise on connectivity quality. Give your users true Ethernet-grade performance with Wi-Fi 6E, which takes wireless speed, performance and reliability to a new level. You get nearly double the speed compared to Wi-Fi 5. Support for the new 6 GHz band that is exclusive to Wi-Fi 6 eliminates interference from wireless technologies that support 2.4 GHz and 5 GHz bands — such as microwave ovens, cordless phones and security cameras. The result? More robust and dependable Wi-Fi connections.

### Rugged and ready for all day use

The display is ball-drop tested to ensure it can withstand the inevitable sudden impacts in public spaces. It's dust-proof and can handle liquids that are sprayed or splashed from any angle. And the anti-smudge display coating is fingerprint resistant.

### Easy, flexible installation options

Reduce deployment time, complexity and cost by eliminating the need for outlets. With Power over Ethernet (PoE) support, power and a wired data connection can be supplied to the KC50 over standard Ethernet cabling — no expensive power drops or unsightly extension cords required. And you can apply pre-established power profiles and customized settings to match different PoE power allocations with OEM Config powered by Mx, further simplifying deployment.

### Add new capabilities with Zebra DNA

Make the KC50 easier to use, secure and manage with the industry's most mature and complete toolkit. Transform Android into an enterprise-class operating system with a choice of over 100 features with Mobility Extensions (Mx). Add an on-screen keyboard designed to simplify data entry with Enterprise Keyboard. Accept barcode data without any coding with DataWedge. Enable two-way push-to-talk calling with Workcloud Communications PTT Pro to enable customers to reach out for assistance. Keep your Android OS version safe with timely updates and bug fixes with Lifeguard<sup>™</sup> for Android. Enterprise Mobility Development Kit (EMDK) for Android and Enterprise Browser make it easy to develop applications that take advantage of all the KC50 features. StageNow lets you stage a handful or thousands of kiosks with a quick scan of a barcode or tap on an NFC tag. And numerous troubleshooting tools make it easy to diagnose and resolve technical issues.

### An exceptional lifecycle

Unlike many devices, the KC50 Kiosk Computer will be available for sale for four years, eliminating the cost and complexity of mixed model deployments. And with service extended for an additional four years, you get up to eight total years of service and support, providing an unmatched return on investment.

## **Specifications**

### **Physical Characteristics**

Dimensions	15 in: 15.17 in L x 9.43 in W x 1.51 in H 15 in: (385.2mm L x 239.4mm W x 38.3mm H)	Motion Sensor	3-axis gyroscope; 3-axis accelerometer	
	22 in: (363.2fmH L x 259.4mm W x 38.3mm H) 22 in: 20.35 in L x 12.56 in W x 1.70 in H 22 in: (516.8mm L x 319.0mm W x 43.3mm H)	Data Capture		
Weight	15 in: 5.7 lbs (2.6kg) 22 in: 11.6 lbs (5.3kg)	Scanning	Optional SE4720 1D/2D decoded imager	
Display	22 in: 21.5 in. Full High Definition; 1080 x 1920; LED backlight; 300 NITS; optically	Front Camera	Z-Flex Accessory 5 MP	
bonded to touch panel 15 in: 15.6 in. Full High Definition; 1080 x 1920; LED backlight; 300 NITS; optically bonded to touch panel		Wireless LAN		
Touch Panel	2.0mm thick Alkali-Aluminosilicate chemically strengthened cover glass; fingerprint resistant anti-smudge coating; multi-mode capacitive touch with bare or gloved fingertip input or conductive stylus (sold separately)	Radio	IEEE 802.11 a/b/g/n/ac/ax/d/h/i/r/k/v/w/mc; 2x2 MU-MIMO; Tri-band (2.4 GHz, 5 GHz, 6 GHz); Wi-Fi CERTIFIED 6™ (Wi-Fi 6E); Dual Band Simultaneous; IPv4, IPv6	
Expansion	MicroSD card supports up to 2 TB	Data Rates	2.4 GHz: 802.11b/g/n/ax — 20 MHz — up to	
Connectivity	USB-C with DP ALT Mode for secondary display		286.8 Mbps; 5 GHz: 802.11a/n/ac/ax — 20 MHz, 40 MHz, 80 MHz, 160 MHz — up to 2402 Mbps; 6 GHz: 802.11ax — 20 MHz, 40 MHz, 80 MHz,	
Network Connections	WLAN (Wireless Local Area Networks) 10/100/1000 Ethernet via RJ45 connector		160 MHz — up to 2402 Mbps	
Notifications	Audible tone; haptic feedback; optional Z-Flex multi-color LED bar accessory, Power LED	Operating Channels	Channel 1-13 (2401-2483 MHz): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13; Channel 36-165 (5150-5850 MHz): 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165; Channel 1-233: (5925-7125 MHz) Channel Bandwidth: 20, 40, 80, 160 MHzActual operating channels/frequencies and bandwidths depend on regulatory rules	
Keypad	On-screen keypad and enterprise keyboard			
Audio	Two microphones with noise cancellation; Dual 1W speakers			
Buttons	Power and volume up/down buttons		and certification agency.	
Interface Ports	Ethernet RJ45; USB Type A 3.0 Superspeed Host Port; GPIO connector for future expansion with USB 2.0 Host Port	Security and Encryption	WPA3 Enterprise 192-bit mode, GCMP256 — EAP-TLS; WPA3 Enterprise, AES-CCMP-128 — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP, EAP-PWD; WPA3 Personal (SAE), AES-CCMP-128; WPA/WPA2 Enterprise, TKIP and AES-CCMP-128;	
Scanner Support	Support for external USB and Bluetooth Scanners			
Mounting and Stands	VESA 100 or VESA 75 mounting Optional accessories: TD50 15-inch secondary display; Z-Flex SE4720 decoded scanner;		WPA/WPA2 Personal (PSK), TKIP and AES-CCMP-128; Enhanced Open (OWE), AES-CCMP-128; WEP 40 bit and 104 bit	
	Z-Flex Multi-Color LED light bar; desktop/floor/countertop stand accessories with support for printer box, height risers	Certifications	Wi-Fi Alliance Certifications: Wi-Fi CERTIFIED n; Wi-Fi CERTIFIED ac; Wi-Fi CERTIFIED 6 (Wi-Fi 6E); WPA2-Personal; WPA2-Enterprise;	
Performanc	e Characteristics		WPA3-Personal; WPA3-Enterprise (includes 192-bit mode); Protected Management Frames; Wi-Fi Enhanced Open; WMM (Wi-Fi Multimedia); WMM-Power Save; WMM-Admission Control; Voice-Enterprise; Wi (5) Instruct Wi (5) Acids Automatic Management Wi (5) Instruct Wi (5) Acids Automatic Management Wi (5) Instruct Wi (5) Acids Automatic Management Wi (5) Instruct Wi (5) Acids Automatic Management Management (5) Acids Automatic Management (5) Acids	

Sensors

CPU	Qualcomm® 5430 Octa Core chipset 2.1 GHz
Operating System	Android; for supported Android versions, visit: www.zebra.com/android-versions
Memory	Up to 8 GB RAM/128 GB UFS Flash

### **User Environment**

	Operating Temp.	+32F to +104F (0C to +40C)
	Storage Temp.	-40F to +158F (-40C to +70C)
	Humidity	5% to 95% non-condensing
	Sealing	IP65 per IEC 60529
	Vibration	Sine: 4 g's PK(5 Hz to 2 kHz) Random: 6 g RMS (20 Hz to 2 kHz) 60 minute duration per axis, 3 axis

### Wireless PAN

Fast Roam

Bluetooth	Class 2, Bluetooth v5.3 with Bluetooth Low Energy (BLE)
NFC	Center of Display front facing; NFC ISO 14443 Type A and B; Mifare, FeliCa and ISO 15693 cards, NFC Forum tags 2,3,4,5; Host Card Emulation, Contactless Payment Support - Front Tap NFC for optimized contactless payment, VAS (Value Added Services) and Wallet support, Apple ECP1.0 and ECP2.0, Apple VAS and Google Smart Tap certified, VAS Library/SDK

Passpoint

Cisco CCKM; OKC

Wi-Fi Direct; Wi-Fi Agile Multiband; Wi-Fi QoS Management; Wi-Fi Optimized Connectivity;

802.11r Fast BSS Transition; PMK Caching;

### **Markets and Applications**

### **Retail: Grocery and Specialty**

 Self-service product configuration and ordering

- Self checkout
- Item locator/wayfinding
- Price check
- Product information Stock check
- Payment/POS
   Endless aisle

### Hospitality

Food ordering/pick-up
Hotels: check-in/check-out information; book services; restaurant reservations

### Airports/Travel

- Self check-in Baggage tags
- Seat upgrades

### Healthcare

- Check-in/check-out
- Appointment request
- Complete paperwork
- Patient surgery status

#### **Parcel Management**

Package drop off

### Manufacturing

 Visual factories • Signage

### User Environment

Electrostatic Discharge (ESD)	+/- 15 kV air discharge; +/- 8 kV direct discharge; +/- 8 kV indirect discharge
Power	24 VDC Zebra PSU: PWR-BGA24V78W4WW Power profiles: includes predefined or customized configurations for main display brightness, external display connection, speaker, Wi-Fi, Bluetooth, USB and GPIO connectors to meet different power allocations Power over Ethernet: 30W to 90W PSE; IEEE 802.3at/bt; capable of receiving a maximum power of 71 watts from a compliant PoE power supply (support for Class 4 through 8)

Optional Accessories: TD50 15-inch secondary display; Z-Flex SE4720 decoded scanner; Z-Flex Multi-Color LED light bar; desktop/floor/countertop stand accessories with support for printer box, height risers

### Warranty

Subject to the terms of Zebra's hardware warranty statement, the KC50 is warranted against defects in workmanship and materials for a period of one (1) year from the date of shipment. For complete warranty statement, please visit www.zebra.com/warranty

### **Recommended Services**

Eliminate unexpected repair costs with Zebra OneCare™ Essential or Select Maintenance Plans to ensure there's no disruption in your workflows. When it comes to device visibility, we help you make informed decisions with detailed analytics from VisibilityIQ™ Foresight that help identify possible issues before they cause significant problems, ensuring devices are used to their fullest potential. Zebra's Professional Services team can help stage devices with custom images and specific applications prior to deployment. For more information on Zebra services, please visit

www.zebra.com/services

### Zebra DNA

Zebra DNA solutions help you get more value out of your Zebra Android devices by adding functionality as well as simplifying deployment and management. For more information on these Zebra-only features, please visit

www.zebra.com/mobilitydnaZebra DNA is available on Android only. Features may vary by model and a Support Contract may be required. To learn what solutions are supported, please visit: https://developer.zebra.com/mobilitydna



NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations contact.emea@zebra.com Latin America Headquarters zebra.com/locations la.contactme@zebra.com

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. Android is a trademark of Google LLC. All other trademarks are the property of their respective owners. ©2025 Zebra Technologies Corp. and/or its affiliates. 03/05/2025 HTML